AUTOMATIC BEVELLING













J-groove bevelling (option)



Bevel angle from 60 to



Bevel width up to 35mm




Plate thickness max 35mm 36-70mm (option)

A NEW GENERATION AUTO FEED MACHINE WHICH BEVELS STEEL ON TOP, FRONT AND BOTTOM EDGES.

- Auto feed portable beveller
- Continuous adjustable bevel angles between 60 and minus 60 degrees, eliminating the need to turn plate over
- Maximum bevel width (depending on angle) from 28 up to 25mm
- Variable feed control for work on a variety of steel grades and thickness (up to 35mm as a standard or optionally up to 70mm)
- Bevelling in both travel directions
- Motor overload protection
- J-groove bevelling option available
- Optional extendable rails
- Quick set up

CALL 01706 229 490 TO BOOK YOUR DEMONSTRATION NOW OR VISIT WWW.STEELBEAST.CO.UK





STEELS: ® TECHNICAL SPECIFICATIONS



SPECIFICATIONS	
MODEL	ABM28
Motor	1600W
Spindle Speed (without load)	2780 RPM
Bevelling angle	60° to -60°
Maximum bevel width	35mm
Feed speed	250 – 500mm
Plate thickness	Max 35mm (optional 36-70mm)
Length	1211mm
Width	619mm
Height	532mm
Weight (without milling head)	78.5kg
Power Supply	220v/ 50-60Hz

b	35 mm	30 mm	28 mm	30 mm
D	SO IIIIII	30 111111	20 111111	30 111111
Maximi	um bevel			UIS EN
			A SHARE	
width d	epends on			1
the bev	eled angle		60	1000
			1	
				wi _v
		6		No. of Street, or other Persons and the Person
			" » »	
	1		0	Y
1	1			
	-			
No. of the last of			V	
			ASSESSED FOR	
				had
			60	
			ou	
		V	THE RESERVE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TW	

FEATURES

- 1. Carriage mounted on a guide track
- 2. Milling unit
- 3. Milling unit support for bevelling at 60° to 60°
- 4. Additional guide track section
- 5. Track clamp for 10-35mm plates (3pcs)
- 6. Chip container
- 7. Set of tools
- 8. Clamp for 10-35mm thick plates (2pcs)
- Wooden Box
- 10. Operations Manual

BM28MHS-70PF

ACCESSORIES

BM28SMH – Milling Head (7 inserts required)

BM28IS - Cutting Insert (1 Piece, 10 PCS in a Box)

BM28JMHR - J-groove R6 milling head (6 inserts R6 Required)

BM28IJR6 – Cutting Insert for J-groove R6 end preparation

BM28JMHR8 – J-groove R8 milling head (5 inserts R8 required)

BM28IJR8 – Cutting insert for J-groove R8 end preparation

BM28GT – Guide track L=1200mm (47.25")

BM28CP35 – Track clamp for 10 – 35mm thick plates

BM28CP70 – Track clamp for 36 – 70 mm thick plates

BM28C35 – Clamp for 10 – 35mm thick plates

BM28C70 – Clamp for 36 – 70mm thick plates

BM28MHS-35 – Milling unit support for bevelling 10-35mm thick plates from - 60° to 60°

BM28MHS-70PF – Milling unit support for bevelling 36 – 70mm thick plates at 0° to 60° (incl. facing)

BM28MHS-70M – Milling unit support for bevelling 36 – 70mm thick plates at 0° to -60°

BM28AH12 - 120 Angle attachment with height adjustment

BM28AH12

CALL 01706 229 490 TO BOOK YOUR DEMONSTRATION NOW OR VISIT WWW.STEELBEAST.CO.UK



BM28MHS-70M

