


STEELBEAST®

JEI
Solutions
Built for Industry

DRAGON

CUTTING TRACK CARRIAGE




DRAGON FOR OXY-FUEL

Dragon is intended to transport different types of oxy-fuel cutting torches with a grip diameter 28-35mm ,(1-1/8" to 1-3/8") to perform machine quality cutting and beveling processes in a variety of applications.

DRAGON HS FOR PLASMA

High speed plasma cutting and beveling is available by means of Dragon HS.







CALL 01706 229 490 TO BOOK YOUR DEMONSTRATION NOW OR VISIT WWW.STEELBEAST.CO.UK



PRIMARY FEATURES AND BENEFITS

- State-of-the-art, digitally controlled track torch
 - Cutting and beveling up to 45° (also parallel by means of 2 torches)
 - Quick clamping torch holder for torch diameter from 28mm to 35mm
 - Advanced speed control system with implemented digital PID regulator
 - LED display with readout of actual and set speed, and report messages
 - Rigid heat-proof design
 - 2-wheel drive with auto – braking drive unit
 - Quick drive release switch for easy re-positioning
- Runs on a rail or directly on a workpiece
- Connectable rails to form various lengths
 - Wide assortment of optional accessories for variety of applications, like machine barrel torch holders, manifolds, circle cutting attachment etc.




TECHNICAL SPECIFICATIONS

DRAGON FOR OXY-FUEL

DRAGON HS FOR PLASMA

Voltage	~ 115–230 V, 50–60 Hz	~ 115–230 V, 50–60 Hz
Power	20 W	20 W
Operating position	horizontal	horizontal
Torch diameter	28–35 mm (1.10–1.38")	28–35 mm (1.10–1.38")
Ground clearance	8 mm (0.31")	8 mm (0.31")
Speed	0–150 cm/min (0–59 in/min)	10–300 cm/min (4–118 in/min)
Weight	16.8 kg (37.0 lbs)	16.8 kg (37.0 lbs)



CALL **01706 229 490** TO BOOK YOUR DEMONSTRATION NOW OR VISIT **WWW.STEELBEAST.CO.UK**

STANDARD ACCESSORIES FOR BOTH DRAGON AND DRAGON HS



RAM-0475-07-00-00-0
580 mm (22.8") Geared Rack



PWG-0475-09-00-00-0
Counterweight 1.3 kg (2.9 lbs)



UCW-0475-28-00-00-0
Standard Torch Holder with
angle adjustment



Power cord
3m (9,7 ft)

OPTIONAL ACCESSORIES FOR BOTH DRAGON AND DRAGON HS



TRO-0475-13-00-00-0
Track Assembly 1800mm (70,9")
V" Groove Center Line 152mm (6")



ZSP-0475-56-00-00-0
Track Dual Magnetic Unit



RAM-0475-23-00-00-0
1000mm (39,4") Geared Rack



PWG-0475-10-00-00-0
Large Counterweight 2,6kg
(5,7lbs)




ZCS-0475-28-10-00-0
Standard Torch Holder
28-35 mm (1.10-1.38")



UCW-0475-08-00-00-0
Precise Torch Holder with angle
and height adjustment



UCW-0475-15-00-00-1
Slide Rack Holder




PDT-0475-26-00-00-0
Roller Support



PDT-0475-34-00-00-0
Cable Anchor



CYR-0475-22-00-00-0
Circle Cutting Attachment



CALL 01706 229 490 TO BOOK YOUR DEMONSTRATION NOW OR VISIT WWW.STEELBEAST.CO.UK

STANDARD ACCESSORIES FOR BOTH DRAGON AND DRAGON HS



OSL-0475-54-00-00-0
Heat Protection Shield (left)




OSL-0475-55-00-00-0
Heat Protection Shield (right)



OSL-0475-53-00-00-0
Heat Protection Shield (bottom)

OPTIONAL ACCESSORIES FOR OXY-FUEL

GAS MANIFOLD TYPE	METRIC	IMPERIAL
Manifold 2x2	RZD-0475-64-00-00-0	RZD-0475-68-00-00-0
Manifold 2x3	RZD-0475-63-00-00-0	RZD-0475-67-00-00-0
Manifold 3/3	RZD-0475-74-00-00-0	RZD-0475-73-00-00-0
Manifold 2x2 with cut-off valve	RZD-0475-65-00-00-0	RZD-0475-70-00-00-0
Manifold 2/3 with cut-off valve	RZD-0475-66-00-00-0	RZD-0475-69-00-00-0
Manifold 3/3 with cut-off valve	RZD-0475-72-00-00-0	RZD-0475-71-00-00-0




UCW-0475-61-00-00-0
Machine Barrel Torch Holder
φ 30mm (1.18")



UCW-0475-42-00-00-0
Machine Barrel Torch Holder
φ 35mm (1.38")

UCW-0475-59-00-00-0
Precise Machine Torch Holder
φ 30mm (1.18")

UCW-0475-42-00-00-1
Precise Machine Torch Holder
φ 35mm (1.38")




OPTIONAL ACCESSORIES FOR PLASMA DRAGON HS



ZSP-0475-58-00-00-0
Plasma Arc Ignition



KBL-0475-58-05-00-0
Plasma Arc Ignition Cable



CALL **01706 229 490** TO BOOK YOUR DEMONSTRATION NOW OR VISIT WWW.STEELBEAST.CO.UK