

STEELBEASTR




PORTABLE PIPE BEVELLER




Max bevel width 45 mm




Bevel angle from -60° to 60°




Pipe OD Facing off 200-1000 mm




J-groove bevelling




Min. wall thickness 5mm



Pipe ID bevelling




Pipe OD bevelling



Facing of





STAINLESS STEELS MACHINING IS NOW POSSIBLE.

PB40-PBS IS DESIGNED FOR BEVELING AND FACING PIPES, TANKS OR TUBES IN A RANGE OF DIAMETERS FROM 200 MM TO 1000 MM (8-40").

High-speed rotary milling head with replaceable inserts enables effective and efficient machining with bevel widths up to 45 mm (1-3/4") and angles between 0° and 60°.

Internal beveling and J-groove end preparation is optionally available. Use of heavy duty milling head in PB40-PBS offers accurate bevels in a fraction of the time compared to traditional single point machining. This feature saves time and money by excellent efficiency.



STEEESEAST® TECHNICAL SPECIFICATIONS




PB40-PBS Technical specification	
Power supply	1~ 208 – 230 V, 50/60 Hz 3~ 208 – 230 V, 50/60 Hz
External pipe diameter range	200-1000 mm (8"- 40") pipes longer than 830 mm; 200-600 mm (8"- 23-5/8") pipes of 400-830 mm length
Maximum allowed pipe weight	10 000 kg (22 000 lbs)*, if active support equipped with optional steel rollers
Min. pipe wall thickness	5 mm (3/16")
Pipe fixing	mechanical with chain
Feed rate	100-1100 mm/min
Beveling angle range	0-60° with continuous angle adjustment
Max OD bevel width	45 mm (1-3/4")
Max ID bevel width	5 mm (1/4") standard, up to 20 mm ("13/16) - option
Beveling type "J"	YES - option
"J" type beveling radius	0.24 in./6 mm or 0.31 in./8 mm
Product Code	PB40-PBS

^{* 6000} kg (13 200 lbs) for plastic rollers of active support (standard)


STANDARD SHIPPING SET


- Stationary pipe beveling machine
- Active support (with plastic rollers)
- Passive support (with steel rollers)
- Standard milling head with 7 cutting inserts
- Set of guiding chains
- 10 mm hex wrench
- 8 mm hex wrench
- 5 mm hex wrench
- Torx T15P screwdriver
- Operator's Manual
- Wooden box

Range of diameters from 200 mm up to 1000 mm (8-40")




DIMENSIONS





Operations with optional milling heads








STEELBEAST® ACCESSORIES



BEVELLING - STANDARD ACCESSORIES



BM28MH Standard Milling head (7 inserts required)



BM21IS
Cutting insert for beveling
1pc (sold 10pcs/box)



BM21ISHD
Cutting insert HD for beveling
1pc (sold 10pcs/box)



BM21-41 Insert fixing screw for PLY-000282/PLY-000591

J-GROOVE BEVELLING OPTION



PB40MHR6 J-groove R6 milling head (6 inserts R6 required)



PB40IR6 Cutting insert for J groove R6 end preparation 1pc (sold 10pcs/box)



PB40MHSR6 Insert fixing screw for PLY-000198



PB40MHR8 J-groove R8 milling head (5 inserts R8 required)



PB40IR8
Cutting insert for J groove R8 end preparation 1pc (sold 10pcs/box)




PB40MHSR8 Insert fixinig screw for PLY-000201

INTERNAL BEVELLING OPTION



PB40MHIB Milling head for internal beveling



BM21IS
Cutting inserts for beveling
1pc (sold 10pcs/box)



PLY-000282 Insert fixing screw for PLY-000282











BEVELLING OF SHORT PIPES, OVAL PIPES & PIPES UP TO 10 TONNES






DCS-0436-12-00-00-0 Clamping device for short pipes of 400-830 mm length



WSP-0436-24-00-00-0
Oval pipe tracking attachment
Available either with brand new
machine or for retrofitting



KOL-0436-23-00-00-0 Steel roll for active pipe support 1pc (4pcs required)


STAINLESS STEELS BEVELING OPTION



LNC-0436-25-01-00-0 Set of guiding chains for Stainless Steel



DCS-0436-25-10-00-0 Clamping device for short Stainless Steel pipes



KOL-000077 Wheel with Vulkollan tire 1pc (2 pcs needed)




RLK-0436-25-11-00-0 Stainless Steel roll for oval pipe tracking attachment



USER-FRIENDLY CONTROL PANEL



SHIELDS AND INTERNAL LIGHTING INCREASE SAFETY AND COMFORT OF THE OPERATOR



ADJUSTABLE CHAIN (Ø 200-1000 MM) ENSURES POSITIVE AXIAL ROTATION



HEAVY-DUTY ADJUSTABLE PIPE SUPPORT (Ø 200-1000 MM)

