



Stationary beveller for machining straight edges of different size workpieces. Modern design, numbers of advanced control systems and innovative solutions streamlines workflow to maximize your production efficiency.

CALL 01706 229 490 TO BOOK YOUR DEMONSTRATION NOW OR VISIT WWW.STEELBEAST.CO.UK



## STEELBEAST® WHY THE SBM-500?



- Workpiece height up to 100 mm
- Powerful 7.500 W motor
- 3D contact wheel control ensures proper workpiece alignment in relation to milling head
- Ergonomic ball roller bench
- Swarf drawer
- Supplementary tables to ccommodate long workpieces
- ✓ Pipe beveling attachment for pipes 50-150 mm (2-6") OD

- Very high surface quality
- Continuous adjustment of spindle speed and feed rate make it suitable for different types of steel and aluminum
- Precise setting of bevel angle from 15 up to 60 degrees and bevel width up to 30 mm
- ✓ High speed rotary milling head equipped with 10 inserts
- Cutting inserts dedicated to various materials
- ✓ No heat affected zones or distortion of the workpiece



CONVENIENT BALL ROLLER BENCH



SUITABLE FOR VARIOUS MATERIALS INCLUDING ALUMINUM



AUXILIARY TABLES TO ACCOMMODATE LONG WORKPIECES



POSSIBILITY OF PIPE OD BEVELLING

WWW.JEIUK.COM



USER-FRIENDLY CONTROL PANEL



EASY ACCESS TO MILLING HEAD AND INSERTS

CALL 01706 229 490 TO BOOK YOUR DEMONSTRATION NOW OR VISIT WWW.STEELBEAST.CO.UK






## STEELBEAST® TECHNICAL SPECIFICATIONS









PRECISE BEVEL ANGLE ADJUSTMENT

HIGH QUALITY BEVEL RESULTS

SIMPLE SETTING OF BEVEL WIDTH

## **ACCESSORIES**


- Milling head (GLW-000030)
- Cutting insert for steel (10pcs required) (PLY-000396)
- Cutting insert for aluminum (10pcs required) (PLY-000408)
- Insert screw (SRB-000418)
- Shim (PLY-000439)
- Shim screw (SRB-000417)
- Auxiliary table for long workpieces (STL-0573-37-00-00-0)
- ▼ Pipe bevelling attachment for pipes 50-150 mm (2-6") OD (PRK-0573-36-00-00-0)

STANDA	۱RN	<b>SHIPI</b>	DING	<b>SFT</b>
JIANUF	anu	JIIII I	1111	OLI

- SBM-500
- Set of tools
- Operator's manual (English)

Cutting inserts for stainless steel are available on request

VOLTAGE	3~ 400 VAC + N+PE, 50/60 Hz
POWER	7500 W
SPINDLE SPEED (No load)	500-2920 rpm
FEED RATE	up to 3.3m/min
FEED BY CONTACT WHEEL	YES
BEVEL ANGLE RANGE	15 - 60° with continuous angle adjustment
BEVEL WIDTH	up to 30 mm
MILLING HEAD WITH 10 INSERTS	YES
MIN. DIMENSIONS OF A BAR	50 x 150 x 3mm
MAX. WORKPIECE HEIGHT	up to 100mm
WEIGHT	850 kg
PRODUCT CODE	UKS-0573-10-00-00-0



CALL 01706 229 490 TO BOOK YOUR DEMONSTRATION NOW OR VISIT WWW.STEELBEAST.CO.UK

