STEELBERST® MINI SPIDER

CORDLESS WELDING TRACTOR



A 4-wheel drive system combined with a permanent magnetic base ensures strong traction and smooth, consistent travel. Precise speed control and stabilisation allow the operator to perfectly match weld bead geometry to the required specification, minimising over-welding and significantly reducing filler metal usage.

For added flexibility, the torch mounting assembly can be easily switched to either side of the tractor, allowing uninterrupted welding along the entire length of the workpiece.

Features and benefits:

Compact, lightweight design: ideal for welding in narrow or confined spaces

18 V DC battery power: uses the same battery as our other cordless tractors for complete compatibility

Cable-free operation: no mains power required, improving mobility and reducing setup time

Intelligent battery management: ensures reliable, long-lasting performance in demanding conditions

Digital LED display: enables quick travel speed presets & provides diagnostic messages for easy monitoring

Easy battery access: check charge levels at a glance

Adjustable guide rollers: built-in and height-adjustable for stable and precise tracking **Reversible torch mounting:** allows torch placement on either side for flexible operation

Edge-to-edge welding: perfect for continuous fillet welds, such as stiffener welding in bridge structures

Consistent heat input: minimises distortion and ensures uniform weld quality

Advanced battery control system

Detection and supervised parameters:

- · too low and too high voltage
- too low and too high temperature
- failure of the temperature sensor
- · internal battery failure

Benefits:

- over discharge protection
- extended battery life
- · high level of safety for both tractor and operator









Continuous welding



Horizontal speed 0-110 cm/min



Torch placement on either side



Welding in narrow spaces



Weight 6.6 kg

STEELBEAST® INI SPIDER

CORDLESS WELDING TRACTOR


FOR MORE INFO SCAN HERE






MINI SPIDER BATTERY Technical Specification	
Voltage	18 V DC, 4.0 Ah
Power	25 W
Welding position (according to EN ISO 6947 & AWS/ASME)	PB / 2F PA / 1F
Torch diameter	16-22 mm (0.63-0.87'')
Min. workpiece thickness	4 mm (0.16")
Ground clearance	4 mm (0.16")
Horizontal pulling force	150 N
Horizontal speed *	0-110 cm/min (0-43.3 in/ min)
Cross slide adjustment range	0-21 mm (0-0.83'') up down, left-right
Weight (w/o battery)	6.6 kg (14.6 lbs)

Dimensions:







Horizontal control panel with clear display and easy adjustment knobs.

Side-mounted battery for better balance and easy access to charge level.



Undercut shielding designed for smooth multi-pass welding and minimised collision risk.



Height-adjustable guide rollers in a range of 13 mm

* With battery fully charged



Torch holder ZCS-0270-42-00-00-0



Bracket for opposite torch placement DYS-0759-08-00-00-0



Battery 4.0 Ah AKM-0738-10-00-01-0 (2 pcs included)

Optional accessories:



Universal cross slide ZSP-0759-07-00-00-0



Enlarged cross slide bracket WSP-0759-12-01-00-0



Auxiliary magnet blocks ZSP-0759-10-00-00-0



Cable anchor PDT-0526-21-00-00-0

Standard configuration allows torch mounting on either side: left or right, with no additional accessories required.



Cross-slide with torch holder on the left



Universal cross slide with torch holder and bracket included in the standard delivery set.



Cross-slide with torch holder on the right



LDW-0738-04-00-30-0

Optional cross slide is required if the operator wants the tractor ready to hold a torch on both sides.



Torch to be hold on one side



Optional universal cross-slide



Torch to be hold on both sides

Standard shipping set:

Tractor Plastic box Bracket 3 mm hex wrench 4 mm hex wrench 5 mm hex wrench Battery 4.0 Ah (2 pcs) Operator's manual